

Report No.: 27242903a 001

Page 1 of 55

Client: SHANTOU VEITCH FAIRYTALES TRADING CO., LTD.

Contact Information: 5th floor, No. 5, Binjiang Road 2nd Road, Chenghua Street, Chenghai District, Shantou City, Guangdong Province, China, 515800

Manufacturer's name: SHANTOU VEITCH FAIRYTALES TRADING CO., LTD.

Identification/ Model No(s): TOYS

Please refer to page 3-5.

Sample obtaining method: Sending by customer

Condition at delivery: Test item complete and undamaged.

Sample Receiving date: 2026-06-29, 2026-07-21

Testing Period: 2026-07-07 to 2026-07-28

Place of testing: Chemical laboratory Shenzhen, Toys laboratory Shenzhen

Test Specification:

Please refer to "Test Result Summary List" on page 2 for details

Other information:

(1) The provided age grade of the item(s) : For age of over 3 years.

The appropriate age grade of the item(s) : For age of over 10 months (baby).

For all ages (dog).

For age of over 3 years (others).

As per client's request, the item(s) was/ were tested for the age of over 3 years.

(2) Packaging provided: Artwork

For and on behalf of
TÜV Rheinland (Shenzhen) Co., Ltd.



Candy He/
Lab. Supervisor

2026-07-29

Date

Name/Position



Gray Z. D. Zhang/
Technical Manager

2026-07-29

Date

Name/Position

Sample information is provided by customer. Test result is drawn according to the kind and extent of tests performed.

This test report relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.

"Decision Rule" document announced in our website (<https://www.tuv.com/landingpage/en/qm-gcn/>) describes the statement of conformity and its rule of enforcement for test results are applicable throughout this test report.

Test Report No.: 27242903a 001

Page 2 of 55

Test Result Summary :**Test Specification:**

- 1 EN 71-1:2014+A1:2018 Mechanical and physical properties
- 2 EN 71-1:2026 Mechanical and physical properties
- 3 2009/48/EC CE marking
- 4 2009/48/EC Labeling Requirement(Importer/ Manufacturer Mark, Product Identification, Washing/ Cleaning instruction)
- 5 EN 71-2:2020 Flammability
- 6 EN 71-2:2020+A1:2025 Flammability
- 7 BS EN 71-1:2014+A1:2018 Mechanical and physical properties
- 8 BS EN 71-1:2026 Mechanical and physical properties
- 9 The Toys (Safety) Regulations 2011 of UK, UKCA mark
- 10 The Toys (Safety) Regulations 2011 of UK, labelling requirements
- 11 BS EN 71-2:2020 Flammability
- 12 BS EN 71-2:2020+A1:2025 Flammability
- 13 EN 71-3:2019+A2:2024 / BS EN 71-3:2019+A2:2024 Migration of certain elements - with reference to 2009/48/EC and its amendments
- 14 EN IEC 62115:2020+A11:2020
Electric toys - Safety
- 15 Safety Of Children's Clothing - Cords And Drawstrings On Children's Clothing

Test result:

PASS

PASS

PASS

Please refer to result page

PASS

PASS

PASS

PASS

PASS

Please refer to result page

PASS

PASS

PASS

PASS

PASS

Test Report No.: 27242903a 001

Page 3 of 55

Information provided by customer:

SP01-1,SP01-2,SP01-3,SP01-4,SP01-5,SP01-6,SP01-7,SP01-8,SP01-9,SP01-10,SP01-11,SP01-12,SP01-13,SP02-1,SP02-2,SP02-3,SP02-4,SP02-5,SP02-6,SP02-7,SP02-8,SP02-9,SP02-10,SP02-11,SP02-12,SP03-1,SP03-2,SP03-3,SP03-9A,SP03-9B,SP03-9C,SP07-7,SP07-8,SP07-9,SP07-10,SP07-11,SP07-12,SP07-13,SP07-14,SP07-15,SP07-16,SP07-17,SP07-18,SP07-19,SP07-20,SP07-21,SP07-22,SP07-23,SP07-24,SP07-25,SP07-26,SP07-27,SP10-1A,SP10-1B,SP10-1C,SP10-1D,SP10-1E,SP10-2A,SP10-2B,SP10-2C,SP10-2D,SP10-2E,SP10-3A,SP10-3B,SP10-4A,SP10-4B,SP10-5A,SP10-5B,SP10-5C,SP10-6A,SP10-6B,SP10-6C,SP10-6D,SP10-6E,SP10-7A,SP10-7B,SP10-7C,SP10-7D,SP10-8A,SP10-8B,SP10-8C,SP10-8D,SP10-9,SP10-10,SP10-11,SP10-12,SP10-13,SP10-14,SP10-15,SP10-16,SP10-17,SP10-18,SP10-19,SP20-1A,SP20-1B,SP20-1C,SP20-1D,SP20-1E,SP24-1A,SP25-1A,SP25-1B,SP25-3A,SP25-3B,SP25-3C,SP25-3D,SP25-4A,SP25-4B,SP25-5A,SP25-5B,SP25-6,SP25-7,SP25-8A,SP25-8B,SP25-8C,SP25-8D,SP25-9A,SP25-9B,SP25-9C,SP25-10,SP25-11,SP25-12,SP25-13,SP25-14,SP25-15,SP25-16,SP25-17,SP25-18,SP25-19,SP25-20,SP25-21,SP25-22,SP26-1A,SP26-1B,SP26-1C,SP26-1D,SP26-2,SP28-1,SP28-1A,SP28-1B,SP28-1C,SP28-1D,SP28-1E,SP28-2,SP28-2A,SP28-2B,SP28-2C,SP28-2D,SP28-2E,SP28-2F,SP28-2G,SP28-3A,SP28-3B,SP28-3C,SP28-3D,SP28-4A,SP28-4B,SP28-4C,SP28-4D,SP28-4E,SP28-4F,SP28-4G,SP28-4H,SP28-4I,SP28-4J,SP28-6A,SP28-6B,SP28-6C,SP28-7A,SP28-7B,SP28-7C,SP28-7D,SP28-7E,SP29-1,SP29-2,SP29-3,SP29-4,SP34-1A,SP34-1B,SP34-1C,SP34-1D,SP34-1E,SP34-2,SP34-4A,SP34-4B,SP34-10,SP35-1,SP37-1,SP38-1A,SP38-1B,SP38-1C,SP39-1A,SP39-1B,SP39-2A,SP39-2B,SP39-3A,SP39-3B,SP40-1A,SP40-1B,SP40-1C,SP40-1D,SP40-2A,SP40-2B,SP40-2C,SP40-2D,SP40-3A,SP40-3,SP40-4,SP40-5,SP40-6,SP40-7,SP40-8,SP40-9A,SP40-9B,SP40-9C,SP40-9D,SP40-9E,SP41-1A,SP41-1B,SP41-1C,SP41-1D,SR41-2A,SP41-2B,SP41-2C,SP41-2D,SR41-3A,SP41-3B,SP41-3C,SP41-4A,SP41-4B,SP41-4C,SP41-4D,SR41-4E,SP41-5A,SP41-5B,SP41-5C,SP41-5D,SP41-5E,SP41-6A,SP41-6B,SP41-6C,SP41-6D,SP41-6E,SP41-7,SP42-1,SP42-2,SP42-3,SP42-4,SP42-5,SP42-6,SP42-7,SP42-8,SP42-9,SP43-1,SP43-2,SP43-3,SP43-4,SP43-5,SP80-1A,SP80-1B,SP80-1C,SP80-1D,SP80-1E,SP80-2A,SP80-2B,SP80-2C,SP80-2D,SP80-2E,SP-ZB01-1,SP-ZB01-2,SP-ZB01-3,SP-ZB01-4,SP-ZB01-5,SP-ZB01-6,SP-ZB01-7,SP-ZB01-8,SP-ZB02-1,SP-ZB02-2,SP-ZB02-3,SP-ZB02-4,SP-ZB02-5,SP-ZB02-6,SP-ZB02-7,SP-ZB02-8,SP-ZB02-9,SP-ZB03-1,SP-ZB03-2,SP-ZB03-3,SP-ZB03-4,SP-ZB03-5,SP-ZB03-6,SP-ZB03-7,SP-ZB03-8,SP-ZB03-9,SP-ZB03-10,SP-ZB03-11,SP-ZB04-1,SP-ZB04-2,SP-ZB04-3,SP-ZB04-4,SP-ZB04-5,SP-ZB04-6,SP-ZB04-7,SP-ZB04-8,SP-ZB04-9,SP-ZB04-10,SP-ZB05-1,SP-ZB05-2,SP-ZB05-3,SP-ZB05-4,SP-ZB05-5,SP-ZB05-6,SP-ZB05-7,SP-ZB05-8,SP-ZB05-9,SP-ZB05-10,SP-ZB05-11,SP-ZB05-12,SP-ZB05-13,SP-ZB05-14,SP-ZB05-15,SP-ZB05-16,SP-ZB06A,SP-ZB06B,SP-ZB06C,SP-ZB06D,SP-ZB06E,SP-ZB06F,SP-ZB06G,SP-ZB06H,SP-ZB06I,SP-ZB07A,SP-ZB07B,SP-ZB07C,SP-ZB07D,SP-ZB07E,SP-ZB07F,SP-ZB07G,SP-ZB08A,SP-ZB08B,SP-ZB08C,SP-ZB08D,SP-ZB08E,SP-ZB08F,SP-ZB08G,SP-ZB08H,SP-ZB08I,SP-ZB09A,SP-ZB09B,SP-ZB09C,SP-ZB09D,SP-ZB09E,SP-ZB09F,SP-ZB09G,SP-ZB09H,SP-ZB09I,SP-ZB10A,SP-ZB10B,SP-ZB10C,SP-ZB10D,SP-ZB10E,SP-ZB10F,SP-ZB10G,SP-ZB10H,SP-ZB11A,SP-ZB11B,SP-ZB11C,SP-ZB11D,SP-ZB11E,SP-ZB11F,SP-ZB11G,SP-ZB11H,SP-ZB12A,SP-ZB12B,SP-ZB12C,SP-ZB12D,SP-ZB12E,SP-ZB12F,

Test Report No.: 27242903a 001

Page 4 of 55

SP-ZB12G,SP-ZB13A,SP-ZB13B,SP-ZB13C,SP-ZB13D,SP-ZB13E,SP-ZB13F,SP-ZB14A,SP-ZB14B,SP-ZB14C,
SP-ZB14D,SP-ZB14E,SP-ZB14F,SP-ZB14G,SP-ZB15A,SP-ZB15B,SP-ZB15C,SP-ZB15D,SP-ZB15E,SP-ZB15F,
SP-ZB15G,SP-ZB16A,SP-ZB16B,SP-ZB16C,SP-ZB16D,SP-ZB16E,SP-ZB16F,SP-ZB16G,SP-ZB17A,SP-ZB17B,
SP-ZB17C,SP-ZB17D,SP-ZB17E,SP-ZB17F,SP-ZB17G,SP-ZB18A,SP-ZB18B,SP-ZB18C,SP-ZB18D,SP-ZB18E,
SP-ZB18F,SP-ZB18G,SP-ZB19-1,SP-ZB19-2,SP-ZB19-3,SP-ZB19-4,SP-ZB19-5,SP-ZB19-6,SP-ZB19-7,SP-ZB19-8,
SP-ZB19-9,SP-ZB20-1,SP-ZB20-2,SP-ZB22-1,SP-ZB22-2,SP-ZB22-3,SP-ZB22-4,SP-ZB22-5,SP-ZB22-6,SP-ZB22-7,
SP-ZB22-8,SP-ZB22-9,SP-P01A,SP-P01B,SP-P01C,SP-P01D,SP-P01E,SP-P01F,SP-P01G,SP-P02A,SP-P02B,SP-P02C,
SP-P02D,SP-P02E,SP-P03A,SP-P03B,SP-P03C,SP-P03D,SP-P03E,SP-P04A,SP-P04B,SP-P04C,SP-P04D,SP-P04E,
SP-P05A,SP-P05B,SP-P05C,SP-P05D,SP-P05E,SP-P05F,SP-P05G,SP-P06A,SP-P06B,SP-P06C,SP-P07,SP-P08,SP-P09,
SP-P10,SP-P11,SP-P12,SP-P13,SP-P14,SP-P15,SP-P16,SP-P17,SP-P18,SP-P19,SP-P20,SP-P21,SP-P22,SP-P23,SP-P24,
SP-P25,SP-P26,SP-P27,SP-P28,SP-P29,SP-P30,SP-P31,SP-P32A,SP-P32B,SP-P32C,SP-P32D,SP-P32E,SP-P33A,
SP-P33B,SP-P33C,SP-P33D,SP-P33E,SP34,SP35,SP36,SP37,SP38,SP-D01A,SP-D01B,SP-D01C,SP-D01D,SP-D01E,
SP-D01F,SP-D01G,SP-D02A,SP-D02B,SP-D02C,SP-D02D,SP-D02E,SP-D02F,SP-H01A,SP-H01B,SP-H01C,SP-H01D,
SP-H01E,SP-H01F,SP-H01G,SP-H01H,SP-T01,SP-T02,SP-T03,SP-T04,SP-T05,SP-T06,SP-T07,SP-T08,SP-T09,SP-T10,
SP-T11,SP-T12,SP-T13,SP-T14,SP-T15,SP-T16,SP-T17,SP-T18,SP-T19,SP-T20,SP-T21,SP-T22,SP-T23,SP-K01,SP-K02,
SP-K03,SP-K04,SP-K05,SP-K06,SP-K07,SP-K08,SP-K09,SP-K10,SP-K11,SP-K12,SP-K13,SP-K14,SP-K15,SP-K16,SP-K17,
SP-K18,SP-K19,SP-K20,SP-K21,SP-K22,SP-K23,SP-K24,SP-K25,SP-K26,SP-L01,SP-L02,SP-L03,SP-L04,SP-L05,SP-L06,
SP-L07,SP-L08,SP-L09,SP-L10,SP-L11,SP-L12,SP-L13,SP-L14,SP-L15,SP-L16,SP-L17,SP-L18,SP-L19,SP-L20,SP-L21,
SP-L22,SP-L23,SP-L24,SP-L01A,SP-L02A,SP-L03A,SP-L04A,SP-L05A,SP-L06A,SP-L07A,SP-L08A,SP-L09A,SP-L10A,
SP-L11A,SP-L12A,SP-L13A,SP-L14A,SP-L15A,SP-L16A,SP-L17A,SP-L18A,SP-L19A,SP-L20A,SP-L21A,SP-L22A,SP-L23A,
SP-L24A,SP-L25,SP-L26,SP-L27,SP-L28,SP-L29,SP-L30,SP-L31,SP-L32,SP-L33,SP-L34,SP-L35,SP-L36,SP-L37,
SP-L38,SP-L39,SP-L40,SP-L41,SP-L42,SP-L43,SP-L44,SP-L45,SP-L46,SP-L47,SP-L48,SP-L49,SP-L50,SP-L51,SP-L52,
SP-L53,SP-L54,SP-L55,SP-L56,SP-L57,SP-L58,SP-L59,SP-L60,SP-L61,SP-L62,SP-L63,SP-L64,SP-C06,SP-C07,SP-C08,
SP-C09,SP-C10,SP-C11,SP-C12,SP-C13,SP-C14,SP-C15,SP-C16,SP-C17,SP-C18,SP-C19,SP-C20,SP-C21,SP-C22,SP-C23,
SP-C24,SP-C25,SP-C26,SP-C27,SP-X01-1,SP-X02-1,SP-X03-1,SP-X04-1,SP-X05-1,SP-X06-1,SP-X01-2,SP-X02-2,
SP-X03-2,SP-X04-2,SP-X05-2,SP-X06-2,SP-X01-3,SP-X02-3,SP-X03-3,SP-X04-3,SP-X05-3,SP-X06-3,SP-X01-4,
SP-X02-4,SP-X03-4,SP-X04-4,SP-X05-4,SP-X06-4,SP-X07,SP-X08,SP-X09,SP-F01A,SP-F01B,SP-F01C,SP-F01D,
SP-F02A,SP-F02B,SP-F02C,SP-F02D,SP-F03A,SP-F03B,SP-F03C,SP-F03D,SP-F04A,SP-F04B,SP-F04C,SP-F04D,
SP-F04E,SP-F04F,SP-F04G,SP-F04H,SP-F04I,SP-F04J,SP-F04K,SP-F04L,SP-F05A,SP-F05B,SP-F05C,SP-F05D,
SP-F05E,SP-F05F,SP-F05G,SP-F05H,SP-F06A,SP-F06B,SP-F06C,SP-F06D,SP-F06E,SP-F06F,SP-F06J,SP-F06K,SP-F06L,
SP-F07A,SP-F07B,SP-F07C,SP-F07D,SP-F07E,SP-F07F,SP-F08A,SP-F08B,SP-F08C,SP-F09A,SP-F09B,SP-F09C,SP-F09D,
SP-F09E,SP-F09F,SP-F10A,SP-F10B,SP-F10C,SP-F10D,SP-F10E,SP-F10F,SP-F11A,SP-F11B,SP-F11C,SP-F11D,SP-F11E,
SP-F11F,SP-F12A,SP-F12B,SP-F12C,SP-F12D,SP-F12E,SP-F12F,SP-DZ01A,SP-DZ01B,SP-DZ01C,SP-DZ01D,SP-DZ02A,
SP-DZ02B,SP-DZ02C,SP-DZ02D,SP-DZ03A,SP-DZ03B,SP-DZ03C,SP-DZ03D,SP-DZ04A,SP-DZ04B,SP-DZ04C,

Test Report No.: 27242903a 001

Page 5 of 55

SP-DZ04D,SP-DZ05A,SP-DZ05B,SP-DZ05C,SP-DZ05D,VF06-1,VF06-2,VF06-3,VF06-1A,VF06-2A,VF06-3A,VF07-1,
VF07-2,VF07-3,VF07-4,VF07-5,VF07-6,VF07-7,VF08-1,VF08-2,VF08-3,VF08-4,VF08-5,VF08-6,VF09-1,VF09-2,VF09-3,
VF10-1,VF10-2,VF10-3,VF10-4,VF10-5,VF10-6,VF10-7,VF10-8,VF10-9,VF10-10,VF10-11,VF10-12,VF10-13,VF10-14,
VF10-15,VF10-16,VF10-17,VF10-18,VF10-19,VF10-20,VF11-1,VF11-2,VF11-3,VF11-4,VF11-5,VF11-6,VF11-7,VF11-8,
VF11-9,VF11-10,VF11-11,VF11-12,VF11-13,VF11-14,VF11-15,VF11-16,VF11-17,VF11-18,VF11-19,VF11-20,VF12-1,
VF12-2,VF12-3,VF12-4,VF12-5,VF12-6,VF12-7,VF12-8,DIY-HD01,DIY-FZ01A,DIY-FZ01B,DIY-FZ01C,DIY-FZ01D,
DIY-FZ01E,DIY-FZ01F,DIY-FZ01A-1,DIY-FZ01B-1,DIY-FZ01C-1,DIY-FZ01D-1,DIY-FZ01E-1,DIY-FZ01F-1,DIY-FZ01A-2,
DIY-FZ01B-2,DIY-FZ01C-2,DIY-FZ01D-2,DIY-FZ01E-2,DIY-FZ01F-2,DIY01A,DIY01B,DIY01C,DIY01D,DIY01E,DIY01F
WQ05-1,WQ05-2,WQ05-3,WQ05-4,WQ05-5A,WQ05-5B,WQ06-1,WQ06-2,WQ06-7A,WQ06-7B,WQ06-8A,WQ06-8B,
WQ07,WQ09,WQ10,WQ12,WQ13-1,WQ13,WQ14-1,WQ14,WQ15-1,WQ15,CL-44,CL-45,CL-46,CL-47,CL-48,CL-49,
CL-50,CL-51,CL-52,CL-53,CL-54,CL-55,CL-56,SP32-1A,SP32-1B,SP32-1C,SP32-2A,SP32-2B,SP32-2C,SP32-3A,
SP32-3B,SP32-3C,SP32-3D,SP32-3E,SP32-4,SP32-5,DIY-HD01,DIY-HD02,DIY-HD03,DIY-HD04,DIY-HD05,DIY-HD06,
DIY-HD07,DIY-HD08,DIY-HD09,DIY-HD10,DIY-HD11,DIY-HD12,DIY-HD13,DIY-HD14,DIY-HD15,DIY-HD16,
DIY-HD17,DIY-HD18,DIY-HD19,DIY-HD20,DIY-HD21,DIY-HD22,DIY-HD23,DIY-HD24,DIY-HD25,DIY-HD26,
DIY-HD27,DIY-HD28,DIY-HD29,DIY-HD30,DIY-HD31,DIY-HD32,DIY-HD33,DIY-HD34,DIY-HD35,DIY-HD36,
DIY-HD37,DIY-HD38,DIY-HD39,DIY-HD40,DIY-FS01,DIY-FS02,DIY-FS03,DIY-FS04,DIY-FS05,DIY-FS06,DIY-FS07,
DIY-FS08,DIY-FS09,DIY-FS010,SP-G01,SP-G02,SP-G03,SP-G04,SP-G05,SP-G06,SP-G07,SP-G08,SP-G09,SP-G10
BW02-1,BW02-2,BW02-3,BW02-4,BW02-5,

Test Report No.: 27242903a 001

Page 6 of 55

Material List:

Item: TOYS
 Please refer to page 3-5.

Material No.	Material	Color	Location
M001-1	Whole Product	Multicolor	TOYS
M001b	Whole Product	Multicolor	Cloak (white mesh style)
M001c	Whole Product	Multicolor	Cloak (red lace style)
M001d-1	Whole Product	Multicolor	Cloak (dark pink plush style)
M001e-1	Whole Product	Multicolor	Cloak (red plush style)
M001f	Whole Product	Multicolor	Dress (yellow style)
M001g	Whole Product	Multicolor	Dress (black style)
M002	Plastic	Blue	Body of shoes
M003	Plastic	Transparent/silver	Vamp with glitter
M004	Textile	Light pink	Bowknot
M005	Textile	Light purple	Sleeve of dress
M006	Textile	Light blue	Jumpsuit
M007	Plastic	Purple	Body of hair blinger
M008	Textile	Dark pink	Cloak
M009	Plastic	Flesh	Head
M010	Plastic	Green	Beads
M011	Textile	White	Edge of cloak
M012	Plastic + printing	Transparent orange/iridescent	Beads

Test Report No.: 27242903a 001

Page 7 of 55

1. EN 71-1:2014+A1:2018 Mechanical and physical properties

Test No:	T002
Material No:	M001-1
4. General requirements	
4.1 Material cleanliness	Pass
4.7 Edges	Pass
4.8 Points and metallic wires	Pass
4.9 Protruding parts	Pass
4.10 Parts moving against each other	Pass
4.11 Mouth-actuated toys and other toys intended to be put in the mouth	Pass
4.14 Enclosures	Pass
4.20 Acoustics	Pass
4.26 Toy disguise costumes	Pass
6. Packaging	Pass
7. Warnings, markings and instructions for use	
7.1 General	Pass
7.2 Toys not intended for children under 36 months	Pass

The clause and/or sub-clause would be indicated only in the test report whichever applicable. The comprehensive result report is available upon request.

Remark:

This clause is applicable to dog and baby only.

^ The manufacturer/trader/applicant has provided the artwork for assessment in this test report.

Test Report No.: 27242903a 001

Page 8 of 55

#2.EN 71-1:2026 Mechanical and physical properties

Test No:		T002
Material No:		M001-1
4. General requirements		
4.1 Material cleanliness		Pass
4.7 Edges		Pass
4.8 Points and metallic wires		Pass
4.9 Protruding parts		Pass
4.10 Parts moving against each other		Pass
4.11 Mouth-actuated toys and other toys intended to be put in the mouth		Pass
4.14 Enclosures		Pass
4.20 Acoustics		Pass
4.26 Toy disguise costumes		Pass
6. Packaging		Pass
7. Warnings, markings and instructions for use		
7.1 General		Pass
7.2 Toys not intended for children under 36 months		Pass

The clause and/or sub-clause would be indicated only in the test report whichever applicable. The comprehensive result report is available upon request.

Remark:

^ The manufacturer/trader/applicant has provided the artwork for assessment in this test report.

The test is not covered by CNAS accreditation.

Test Report No.: 27242903a 001

Page 9 of 55

#3.2009/48/EC CE Marking**Test result:**

Test No:	T002
Material No:	M001-1
CE-marking	Pass

Remark:

^ The manufacturer/trader/applicant has provided the artwork for assessment in this test report.

The test is not covered by CNAS accreditation.

Test Report No.: 27242903a 001

Page 10 of 55

#4.2009/48/EC Labeling Requirement (Importer/ Manufacturer Mark, Product Identification, Washing/ Cleaning instruction)**Test result:**

Test No:	T002
Material No:	M001-1
Importer/ Manufacturer Mark (European Company name and address)+	Present (Package)
Product Identification - type, batch, serial or model number+	Present (Product and Package)
Washing/ Cleaning instruction ^	Not Applicable

Remark:

- + These labeling shall be indicated on the toy, or where that is not possible, on its packaging or in documents accompanying the toys.

The correct adherence to all requirements according to directive 2009/48/EC in regards to the marking (name or trademark and contact address of the manufacturer respectively the marking for identification [type, batch, model or serial no.]) of the toy can only be confirmed by the manufacturer, his delegate or the person who brings it onto the market. The marked article were assessed, however, they can not be evaluated in the frame of this test.

- ^ According to Directive 2009/48/EC, a toy intended for use by children under 36 months must be designed and manufactured in such a way that it can be cleaned. A textile toy shall, to this end, be washable, except if it contains a mechanism that may be damaged if soak washed. The toy shall fulfill the safety requirements also after having been cleaned in accordance with this point and the manufacturer's instructions.

- ** The manufacturer/trader/applicant has provided the artwork for assessment in this test report.

- # The test is not covered by CNAS accreditation.

Test Report No.: 27242903a 001

Page 11 of 55

5. EN 71-2:2020 Flammability**Test result:**

Test No:	T002
Material No:	M001-1
4.1 General requirements	Pass
4.2 Toys to be worn on the head	Pass
4.3 Toy disguise costumes and toys intended to be worn by a child in play	Pass

The clause and/or sub-clause would be indicated only in the test report whichever applicable. The comprehensive result report is available upon request.

Test Report No.: 27242903a 001

Page 12 of 55

#6.EN 71-2:2020+A1:2025 Flammability**Test result:**

Test No:	T002
Material No:	M001-1
4.1 General requirements	Pass
4.2 Toys to be worn on the head	Pass
4.3 Toy disguise costumes and toys intended to be worn by a child in play	Pass

The clause and/or sub-clause would be indicated only in the test report whichever applicable. The comprehensive result report is available upon request.

The test is not covered by CNAS accreditation.

Test Report No.: 27242903a 001

Page 13 of 55

7. BS EN 71-1:2014+A1:2018 Mechanical and physical properties

Test No:	T002
Material No:	M001-1
4. General requirements	
4.1 Material cleanliness	Pass
4.7 Edges	Pass
4.8 Points and metallic wires	Pass
4.9 Protruding parts	Pass
4.10 Parts moving against each other	Pass
4.11 Mouth-actuated toys and other toys intended to be put in the mouth	Pass
4.14 Enclosures	Pass
4.20 Acoustics	Pass
4.26 Toy disguise costumes	Pass
6. Packaging	Pass
7. Warnings, markings and instructions for use	
7.1 General	Pass
7.2 Toys not intended for children under 36 months	Pass

The clause and/or sub-clause would be indicated only in the test report whichever applicable. The comprehensive result report is available upon request.

Remark:

This clause is applicable to dog and baby only.

^ The manufacturer/trader/applicant has provided the artwork for assessment in this test report.

Test Report No.: 27242903a 001

Page 14 of 55

#8.BS EN 71-1:2026 Mechanical and physical properties

Test No:	T002
Material No:	M001-1
4. General requirements	
4.1 Material cleanliness	Pass
4.7 Edges	Pass
4.8 Points and metallic wires	Pass
4.9 Protruding parts	Pass
4.10 Parts moving against each other	Pass
4.11 Mouth-actuated toys and other toys intended to be put in the mouth	Pass
4.14 Enclosures	Pass
4.20 Acoustics	Pass
4.26 Toy disguise costumes	Pass
6. Packaging	Pass
7. Warnings, markings and instructions for use	
7.1 General	Pass
7.2 Toys not intended for children under 36 months	Pass

The clause and/or sub-clause would be indicated only in the test report whichever applicable. The comprehensive result report is available upon request.

Remark:

This clause is applicable to dog and baby only.

^ The manufacturer/trader/applicant has provided the artwork for assessment in this test report.

The test is not covered by CNAS accreditation.

Test Report No.: 27242903a 001

Page 15 of 55

#9.The Toys (Safety) Regulations 2011 of UK, UKCA mark**Test result:**

Test No:	T002
Material No:	M001-1
UKCA-marking	Pass

Remark:

- #1 The UK government will continue to recognise the CE marking, therefore businesses can also use the UKCA marking, giving them flexibility to choose which marking to apply.
- * Although no final packaging has been received, the manufacturer/trader/applicant has confirmed that the above information marked (*) will be shown onto the toy itself and/or packaging of the toy.
- ^ The manufacturer/trader/applicant has provided the artwork for assessment in this test report.
- # The test is not covered by CNAS accreditation.

Test Report No.: 27242903a 001

Page 16 of 55

#10.The Toys (Safety) Regulations 2011 of UK, labelling requirements**Test Result:**

Test No:	T002
Material No:	M001-1
UK Importer Name and Address	Present (Package)

^ The manufacturer/trader/applicant has provided the artwork for assessment in this test report.

The test is not covered by CNAS accreditation.

Test Report No.: 27242903a 001

Page 17 of 55

11. BS EN 71-2:2020 Flammability**Test result:**

Test No:	T002
Material No:	M001-1
4.1 General requirements	Pass
4.2 Toys to be worn on the head	Pass
4.3 Toy disguise costumes and toys intended to be worn by a child in play	Pass

The clause and/or sub-clause would be indicated only in the test report whichever applicable. The comprehensive result report is available upon request.

Test Report No.: 27242903a 001

Page 18 of 55

#12.BS EN 71-2:2020+A1:2025 Flammability**Test result:**

	Test No:	T002
	Material No.	M001-1
4.1 General requirements		Pass
4.2 Toys to be worn on the head		Pass
4.3 Toy disguise costumes and toys intended to be worn by a child in play		Pass

The clause and/or sub-clause would be indicated only in the test report whichever applicable. The comprehensive result report is available upon request.

The test is not covered by CNAS accreditation.

Test Report No.: 27242903a 001

Page 19 of 55

#13. EN 71-3:2019+A2:2024 / BS EN 71-3:2019+A2:2024 Migration of certain elements - with reference to 2009/48/EC and its amendments

Test Method: with reference to EN 71-3:2019+A2:2024 / BS EN 71-3:2019+A2:2024, analyzed by ICP-OES / ICP-MS / LC-ICP-MS/IC-UV/GC-MS.

3) For scraped-off toy materials:
Test Result:

Test No.				T001	T002	T003
Material No.				M002	M003	M004
Test Parameter	Unit	RL	Regulatory Requirement	Result	Result	Result
Aluminium (Al)	mg/kg	10	28,130	< RL	< RL	< RL
Antimony (Sb)	mg/kg	5	560	< RL	< RL	15
Arsenic (As)	mg/kg	5	47	< RL	< RL	< RL
Barium (Ba)	mg/kg	2.5	18,750	< RL	< RL	< RL
Boron (B)	mg/kg	10	15,000	< RL	< RL	< RL
Cadmium (Cd)	mg/kg	1	17	< RL	< RL	< RL
Chromium III (Cr(III))	mg/kg	10	460	< RL	< RL	< RL
Chromium VI (Cr(VI))	mg/kg	0.045	0.053	< RL	< RL	< RL
Cobalt (Co)	mg/kg	2.5	130	< RL	< RL	< RL
Copper (Cu)	mg/kg	2.5	7,700	< RL	< RL	< RL
Lead (Pb)	mg/kg	2.5	23	< RL	< RL	< RL
Manganese (Mn)	mg/kg	2.5	15,000	< RL	< RL	< RL
Mercury (Hg)	mg/kg	2.5	94	< RL	< RL	< RL
Nickel (Ni)	mg/kg	2.5	930	< RL	< RL	< RL
Selenium (Se)	mg/kg	10	460	< RL	< RL	< RL
Strontium (Sr)	mg/kg	2.5	56,000	< RL	< RL	< RL
Tin (Sn)	mg/kg	1.0	180,000	< RL	< RL	< RL
Organic Tin [^]	mg/kg	0.2	12	-	-	-
Zinc (Zn)	mg/kg	10	46,000	< RL	< RL	< RL
Mass of trace amount	mg	--	--	-	-	-

Abbreviation: < = less than
 RL = Reporting Limit
 mg/kg denotes milligram per kilogram
 mg denotes milligram
[^] denotes Organic tin are not necessary to be determined when the Tin concentration is less than calculated limit (3.2 mg/kg) or the components were confirmed to be pure metal

Test Report No.: 27242903a 001

Page 20 of 55

Test Result:

			Test No.	T004	T005	T006
			Material No.	M005	M006	M007
Test Parameter	Unit	RL	Regulatory Requirement	Result	Result	Result
Aluminium (Al)	mg/kg	10	28,130	< RL	< RL	< RL
Antimony (Sb)	mg/kg	5	560	< RL	< RL	< RL
Arsenic (As)	mg/kg	5	47	< RL	< RL	< RL
Barium (Ba)	mg/kg	2.5	18,750	< RL	< RL	< RL
Boron (B)	mg/kg	10	15,000	< RL	< RL	< RL
Cadmium (Cd)	mg/kg	1	17	< RL	< RL	< RL
Chromium III (Cr(III))	mg/kg	10	460	< RL	< RL	< RL
Chromium VI (Cr(VI))	mg/kg	0.045	0.053	< RL	< RL	< RL
Cobalt (Co)	mg/kg	2.5	130	< RL	< RL	< RL
Copper (Cu)	mg/kg	2.5	7,700	< RL	< RL	< RL
Lead (Pb)	mg/kg	2.5	23	< RL	< RL	< RL
Manganese (Mn)	mg/kg	2.5	15,000	< RL	< RL	< RL
Mercury (Hg)	mg/kg	2.5	94	< RL	< RL	< RL
Nickel (Ni)	mg/kg	2.5	930	< RL	< RL	< RL
Selenium (Se)	mg/kg	10	460	< RL	< RL	< RL
Strontium (Sr)	mg/kg	2.5	56,000	< RL	< RL	< RL
Tin (Sn)	mg/kg	1.0	180,000	< RL	< RL	< RL
Organic Tin^	mg/kg	0.2	12	-	-	-
Zinc (Zn)	mg/kg	10	46,000	< RL	< RL	< RL
Mass of trace amount	mg	--	--	-	-	-

Abbreviation:

- < = less than
- RL = Reporting Limit
- mg/kg denotes milligram per kilogram
- mg denotes milligram
- ^ denotes Organic tin are not necessary to be determined when the Tin concentration is less than calculated limit (3.2 mg/kg) or the components were confirmed to be pure metal

Test Report No.: 27242903a 001

Page 21 of 55

Test Result:

			Test No.	T007	T008	T009
			Material No.	M008	M009	M010
Test Parameter	Unit	RL	Regulatory Requirement	Result	Result	Result
Aluminium (Al)	mg/kg	10	28,130	< RL	< RL	< RL
Antimony (Sb)	mg/kg	5	560	< RL	< RL	< RL
Arsenic (As)	mg/kg	5	47	< RL	< RL	< RL
Barium (Ba)	mg/kg	2.5	18,750	< RL	< RL	< RL
Boron (B)	mg/kg	10	15,000	< RL	< RL	< RL
Cadmium (Cd)	mg/kg	1	17	< RL	< RL	< RL
Chromium III (Cr(III))	mg/kg	10	460	< RL	< RL	< RL
Chromium VI (Cr(VI))	mg/kg	0.045	0.053	< RL	< RL	< RL
Cobalt (Co)	mg/kg	2.5	130	< RL	< RL	< RL
Copper (Cu)	mg/kg	2.5	7,700	< RL	< RL	< RL
Lead (Pb)	mg/kg	2.5	23	< RL	< RL	< RL
Manganese (Mn)	mg/kg	2.5	15,000	< RL	< RL	< RL
Mercury (Hg)	mg/kg	2.5	94	< RL	< RL	< RL
Nickel (Ni)	mg/kg	2.5	930	< RL	< RL	< RL
Selenium (Se)	mg/kg	10	460	< RL	< RL	< RL
Strontium (Sr)	mg/kg	2.5	56,000	< RL	< RL	< RL
Tin (Sn)	mg/kg	1.0	180,000	< RL	< RL	< RL
Organic Tin [^]	mg/kg	0.2	12	-	-	-
Zinc (Zn)	mg/kg	10	46,000	< RL	< RL	< RL
Mass of trace amount	mg	--	--	-	-	-

Abbreviation:

- < = less than
- RL = Reporting Limit
- mg/kg denotes milligram per kilogram
- mg denotes milligram
- [^] denotes Organic tin are not necessary to be determined when the Tin concentration is less than calculated limit (3.2 mg/kg) or the components were confirmed to be pure metal

Test Report No.: 27242903a 001

Page 22 of 55

Test Result:

			Test No.	T010	T011
			Material No.	M011	M012
Test Parameter	Unit	RL	Regulatory Requirement	Result	Result
Aluminium (Al)	mg/kg	10	28,130	< RL	< RL
Antimony (Sb)	mg/kg	5	560	< RL	< RL
Arsenic (As)	mg/kg	5	47	< RL	< RL
Barium (Ba)	mg/kg	2.5	18,750	< RL	< RL
Boron (B)	mg/kg	10	15,000	< RL	< RL
Cadmium (Cd)	mg/kg	1	17	< RL	< RL
Chromium III (Cr(III))	mg/kg	10	460	< RL	< RL
Chromium VI (Cr(VI))	mg/kg	0.045	0.053	< RL	< RL
Cobalt (Co)	mg/kg	2.5	130	< RL	< RL
Copper (Cu)	mg/kg	2.5	7,700	< RL	< RL
Lead (Pb)	mg/kg	2.5	23	< RL	< RL
Manganese (Mn)	mg/kg	2.5	15,000	< RL	< RL
Mercury (Hg)	mg/kg	2.5	94	< RL	< RL
Nickel (Ni)	mg/kg	2.5	930	< RL	< RL
Selenium (Se)	mg/kg	10	460	< RL	< RL
Strontium (Sr)	mg/kg	2.5	56,000	< RL	< RL
Tin (Sn)	mg/kg	1.0	180,000	< RL	< RL
Organic Tin [^]	mg/kg	0.2	12	-	-
Zinc (Zn)	mg/kg	10	46,000	< RL	327
Mass of trace amount	mg	--	--	-	-

Abbreviation:

- < = less than
- RL = Reporting Limit
- mg/kg denotes milligram per kilogram
- mg denotes milligram
- [^] denotes Organic tin are not necessary to be determined when the Tin concentration is less than calculated limit (3.2 mg/kg) or the components were confirmed to be pure metal

Remark:

- * Categorization of toys materials is based on the material texture. According to point H.11 of Annex H to EN 71-3:2019+A2:2024 / BS EN 71-3:2019+A2:2024 , cosmetic materials with dry, brittle, powder like or pliable texture such as lipstick and eyeshadow are considered as category I materials. However, as a reminder, it cannot preclude the possibility that some national enforcement authorities might take a more stringent action to treat cosmetic materials as sticky and evaluate according to category II requirement as they are intended to be applied on skin and retained for long time.
- ** According to EN 71-3:2019+A2:2024 / BS EN 71-3:2019+A2:2024 , if the weight of a test portion of toy material is less than 10mg, the analysis of migration of certain elements would not be required. If the weight of a test portion of toy material is between 10mg and 100mg, the analytical results would be calculated as though 100mg of the test portion had been used.

The test is not covered by CNAS accreditation.

Test Report No.: 27242903a 001

Page 23 of 55

14.EN IEC 62115:2020+A11:2020 Electric toys - Safety

Test Method: EN IEC 62115:2020+A11:2020

Power Information :

Component No.	Description	Power Type
T1	SHELL	2X1.5V(LR6) DURACELL Replaceable Battery

EN IEC 62115:2020+A11:2020 Electric toys - Safety

Clause	Assessment
1 Scope	--
2 Normative references	--
3 Definitions	--
4 General requirement	--
5 General conditions for the tests	--
6 Criteria for reduced testing	--
7 Marking and Instructions	PASS (*1)
8 Power input	N.A.
9 Heating and abnormal operation	PASS
10 Electric strength	PASS
11 Electric toys used in water, electric toys used with liquid and electric toys cleaned with liquid	N.A.
12 Mechanical strength	PASS
13 Construction	PASS
14 Protection of cords and wires	PASS
15 Components	PASS (*2)
16 Screws and connections	PASS
17 Clearances and creepage distances	PASS
18 Resistance to heat and fire	PASS
19 Radiation and similar hazards	--
19.2 Optical radiation	N.A.
19.3 Other electromagnetic radiation	N.A.

The clause and/or sub-clause would be indicated only in the test report whichever applicable. The comprehensive result report is available upon request.

N.A. = Not Applicable; N.C. = Not conducted

- 19.2 Optical radiation

Clause	Assessment
19.E.2 Light-emitting diodes (LEDs)	N.A.
19.E.3 Lasers	N.A.
19.E.4 UV-emitting lamps	N.A.
19.E.5 Modulated accessible emission	N.A.

N.A. = Not Applicable; N.C. = Not conducted.

The clause and/or sub-clause would be indicated only in the test report whichever applicable. The comprehensive result report is available upon request.

Remark:

- *1 Only the English version of the marking and instructions were assessed. According to the standard, instruction and other texts required by the standard should be written in the official language(s) of the country in which the product is to be sold.
- *2 Components shall comply with the safety requirements specified in the relevant IEC standards as far as they reasonably apply.

Test Report No.: 27242903a 001

Page 25 of 55

#15.Safety Of Children's Clothing - Cords And Drawstrings On Children's Clothing

Test method : Safety Of Childrens Clothing - Cords And Drawstrings On Childrens Clothing (EN 14682)

Age group : Young child, older children and young persons

Specimen specification : Specimen is classified as garments for young children (person aged from birth to age 7 years, including all children up to and including a height of 134 cm)

Specimen specification : Specimen is classified as garments for older children and young persons (person aged from 7 years up to age 14 years, including all boys of height greater than 134 cm up to 182 cm and girls of height greater than 134 cm up to 176 cm)

M001b

3.1 General

3.1.1 The free ends of drawstrings, functional cords, and tied belts or sashes shall have no knots or three-dimensional embellishments and shall be secured to prevent fraying, for example by heat sealing or bar tacking. The ends may be doubled or folded provided no hazard of entrapment is created. Knots and three-dimensional embellishments along the length of the free ends are not permitted. N/A

3.1.2 Toggles shall only be used on drawstrings with no free ends or decorative cords. N/A

3.1.3 Where drawstrings are permitted, they shall be attached to the garment, for example using a bar tack, in at least one point positioned equidistant from the exit points. N/A

3.1.4 Fixed loops, which protrude from the garment, for example to fasten, or loops on fixed bows, shall be no more than 7.5cm in circumference. Flat loops which do not protrude from the garments, for example for belt loops, shall be no more than 7.5cm in length, between the fixed points of attachment to the garment. P

3.1.5 Zip pullers including any embellishment shall be no longer than 7.5cm in length from zip slider. N/A

3.1.6 Zip pullers with or without embellishment shall not hang below the lower edge of garments designed to finish at the ankle. N/A

3.2 Head, neck and upper chest area on garments for young children

3.2.1 Garments intended for young children shall not be designed, manufactured or supplied with drawstrings or functional cords in the head, neck or upper chest area. N/A

3.2.2 Decorative cords shall not be permitted anywhere on the hood or at the back of the neck. N/A

3.2.3 In other parts of neck and upper chest areas, decorative cords shall have free ends no longer than 7.5cm, shall have no knots, toggles or three dimensional embellishments and shall not be positioned so they can tie across the throat. N/A

Decorative cords shall not be made from elastic cords.

3.2.4 Adjusting tabs are permissible provided that the length is no more than 7.5cm, and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. N/A

Test Report No.: 27242903a 001

Page 26 of 55

M001b

- 3.2.5 Shoulder straps shall be constructed such that, when worn, there shall be no free ends external to the garment. Shoulder straps may be permanently fixed to front and back, or attached to permit adjustment of strap length by for example buttons, press fasteners, provided the free end is inside the garment. The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment is worn.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the shoulder strap, the strap including the loop shall lie flat to the body when worn.

Decorative cords attached to a shoulder strap shall not have free ends longer than 7.5cm and fixed loops shall be no more than 7.5cm in circumference.

- 3.2.6 Halter neck-style garments shall be constructed with no free ends in the neck and throat.

N/A

The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment is worn.

Where a mechanism, for example ring and slider, is used to adjust the length of the halter neck, the strap including the loop shall lie flat to the body when worn.

3.3 Head, neck and upper chest area on garments for older children and young persons

- 3.3.1 Drawstrings shall not have free ends.

N/A

Drawstrings with no free ends shall have no protruding loop when the garment is open to its largest and laid flat. When the garment opening is at its smallest, i.e. the size it is intended to fit, maximum protruding loop circumference shall be 15cm.

Where toggles are used for adjustment of drawstrings with no free ends, the toggle shall be fixed to the garment.

- 3.3.2 Functional cords shall be not more than 7.5cm in length. Functional cords shall not be made from elastic cords.

N/A

- 3.3.3 Decorative cords shall not be more than 7.5cm in length including any attachment or three dimensional embellishment. Decorative cords shall not be made from elastic cords.

N/A

- 3.3.4 Adjusting tabs are permissible provided that the length is no more than 7.5cm, and shall have no button, toggle, buckle on the free end which may present an entrapment hazard.

N/A

- 3.3.5 Shoulder straps are permissible provided any free ends are no longer than 14cm from the point at which they are to be tied and fixed loops are no more than 7.5cm in circumference.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the shoulder straps, the strap including the loop shall lie flat to the body when worn.

Test Report No.: 27242903a 001

Page 27 of 55

M001b

- 3.3.6 Halter neck-style garments shall be constructed with no free ends at the neck and throat. The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment worn.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the halter neck strap, the strap including the loop shall lie flat to the body when worn.

3.4 Chest and waist area

- 3.4.1 Garments worn from waist down without shoulder straps, braces, or sleeves, such as trousers, shorts, skirts, briefs, bikini bottoms, shall not have:

a) Free ends of drawstrings longer than 20cm at each end when the garment is in a relaxed natural state;

N/A

b) Protruding loops on drawstrings with no free ends, when the garment is open to its largest and laid flat. Where toggles are used for adjustment of drawstrings with no free ends, the toggles shall be fixed to the garment;

N/A

c) Functional cords longer than 20cm;

N/A

d) Decorative cords longer than 14cm including any embellishment.

N/A

- 3.4.2 Garments other than those listed in 3.4.1 such as shirts, coats, dresses, and dungarees shall not have:

a) Free ends of drawstrings longer than 14cm at each end when the garment is open to its largest and laid flat;

N/A

b) Protruding loops on drawstrings with no free ends when the garment is open to its largest and laid flat. Where toggles are used for adjustment of drawstrings with no free ends, the toggles shall be fixed to the garment;

N/A

c) Functional cords longer than 14cm;

N/A

d) Decorative cords longer than 14cm including any embellishment.

N/A

- 3.4.3 For all garments, adjusting tabs in the waist area shall be a maximum of 14cm.

N/A

- 3.4.4 For young children, tied belts or sashes intended to be tied at the back of the garment are permissible provided that when untied and measured from the point where they are to be tied, they shall be no more than 36cm in length. When untied, they shall not hang below the hem of the garment.

N/A

- 3.4.5 For older children and young persons, tied belts or sashes intended to be tied at the back of the garment are permissible provided that, when untied and measured from the point where they are to be tied they shall be no more than 36cm in length.

N/A

- 3.4.6 For both age groups, tied belts or sashes intended to be tied at the front or at the side of the garment shall be acceptable provided that when untied they shall be no more than 36cm in length measured from the point where they are to be tied.

N/A

3.5 Lower hems of garments which hang below the crotch

Test Report No.: 27242903a 001

Page 28 of 55

M001b

- | | | |
|------------|---|-----|
| 3.5.1 | Drawstrings, functional cords or decorative cords including any toggle shall not hang below the lower edge of the garment. | N/A |
| 3.5.2 | Drawstrings, functional cords or decorative cords at the lower edges of garments shall lie flat against the garment, when the garment is tightened or fastened. | N/A |
| 3.5.3 | In garments that are designed to finish at the ankle such as trousers, skirts or coats, the drawstrings, functional cords and decorative cords at the lower edge shall not be outside the garment. | N/A |
| 3.5.4 | Adjusting tabs shall be no longer than 14cm, shall not hang below the lower edge of the garment and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. | N/A |
| 3.6 | Back area | |
| 3.6.1 | Children's garments shall not be designed to have drawstrings or functional cords that emerge from the back of the garment or to be tied at the back. | N/A |
| 3.6.2 | Decorative cords shall not be more than 7.5cm in length and shall have no knot, toggle or three dimensional embellishment. | N/A |
| 3.6.3 | Adjusting tabs shall be no longer than 7.5cm, shall not hang below the lower edge of the garment and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. | N/A |
| 3.6.4 | Tied belts or sashes are permissible (see 3.4.4 and 3.4.5). | N/A |
| 3.7 | Sleeves | |
| 3.7.1 | Drawstrings, functional cords and decorative cords at the lower edge of long sleeves shall not be outside the garment, when the garment is fastened. | N/A |
| 3.7.2 | Drawstrings, functional cords and decorative cords positioned below the elbow on long sleeves, shall not hang below the lower edge and free ends shall be no longer than 7.5cm. | N/A |
| 3.7.3 | For younger children, drawstrings, functional cords and decorative cords are permissible on short sleeves provided the sleeve finishes above the elbow and the maximum protruding length is 7.5cm measured when the sleeve is open to its largest and laid flat. | N/A |
| 3.7.4 | For older children and young persons, drawstrings, functional cords and decorative cords are permissible on short sleeves provided the sleeve finishes above the elbow and the maximum protruding length is 14cm measured when the sleeve is open to its largest and laid flat. | N/A |
| 3.7.5 | For both age groups, adjusting tabs are permissible on sleeves provided that they are no longer than 10cm in length and when open shall not hang below the edge of the sleeve. | N/A |
| 3.8 | Other parts of the garment | |

Test Report No.: 27242903a 001

Page 29 of 55

M001b

In all other areas of the garment, not previously addressed, the drawstring or functional and decorative cords shall protrude by no more than 14cm when the garment is open to its largest and laid flat.

N/A

Observation

No non-conformance to the requirements for EN 14682:2014 observed

Conclusion

Pass (Material M001b. It complies with the requirements for EN 14682:2014)

M001c**3.1 General**

3.1.1 The free ends of drawstrings, functional cords, and tied belts or sashes shall have no knots or three-dimensional embellishments and shall be secured to prevent fraying, for example by heat sealing or bar tacking. The ends may be doubled or folded provided no hazard of entrapment is created. Knots and three-dimensional embellishments along the length of the free ends are not permitted.

N/A

3.1.2 Toggles shall only be used on drawstrings with no free ends or decorative cords.

N/A

3.1.3 Where drawstrings are permitted, they shall be attached to the garment, for example using a bar tack, in at least one point positioned equidistant from the exit points.

N/A

3.1.4 Fixed loops, which protrude from the garment, for example to fasten, or loops on fixed bows, shall be no more than 7.5cm in circumference. Flat loops which do not protrude from the garments, for example for belt loops, shall be no more than 7.5cm in length, between the fixed points of attachment to the garment.

P

3.1.5 Zip pullers including any embellishment shall be no longer than 7.5cm in length from zip slider.

N/A

3.1.6 Zip pullers with or without embellishment shall not hang below the lower edge of garments designed to finish at the ankle.

N/A

3.2 Head, neck and upper chest area on garments for young children

3.2.1 Garments intended for young children shall not be designed, manufactured or supplied with drawstrings or functional cords in the head, neck or upper chest area.

N/A

3.2.2 Decorative cords shall not be permitted anywhere on the hood or at the back of the neck.

N/A

3.2.3 In other parts of neck and upper chest areas, decorative cords shall have free ends no longer than 7.5cm, shall have no knots, toggles or three dimensional embellishments and shall not be positioned so they can tie across the throat.

N/A

Decorative cords shall not be made from elastic cords.

3.2.4 Adjusting tabs are permissible provided that the length is no more than 7.5cm, and shall have no button, toggle, buckle on the free end which may present an entrapment hazard.

N/A

M001c

- 3.2.5 Shoulder straps shall be constructed such that, when worn, there shall be no free ends external to the garment. Shoulder straps may be permanently fixed to front and back, or attached to permit adjustment of strap length by for example buttons, press fasteners, provided the free end is inside the garment. The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment is worn.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the shoulder strap, the strap including the loop shall lie flat to the body when worn.

Decorative cords attached to a shoulder strap shall not have free ends longer than 7.5cm and fixed loops shall be no more than 7.5cm in circumference.

- 3.2.6 Halter neck-style garments shall be constructed with no free ends in the neck and throat.

N/A

The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment is worn.

Where a mechanism, for example ring and slider, is used to adjust the length of the halter neck, the strap including the loop shall lie flat to the body when worn.

3.3 Head, neck and upper chest area on garments for older children and young persons

- 3.3.1 Drawstrings shall not have free ends.

N/A

Drawstrings with no free ends shall have no protruding loop when the garment is open to its largest and laid flat. When the garment opening is at its smallest, i.e. the size it is intended to fit, maximum protruding loop circumference shall be 15cm.

Where toggles are used for adjustment of drawstrings with no free ends, the toggle shall be fixed to the garment.

- 3.3.2 Functional cords shall be not more than 7.5cm in length. Functional cords shall not be made from elastic cords.

N/A

- 3.3.3 Decorative cords shall not be more than 7.5cm in length including any attachment or three dimensional embellishment. Decorative cords shall not be made from elastic cords.

N/A

- 3.3.4 Adjusting tabs are permissible provided that the length is no more than 7.5cm, and shall have no button, toggle, buckle on the free end which may present an entrapment hazard.

N/A

- 3.3.5 Shoulder straps are permissible provided any free ends are no longer than 14cm from the point at which they are to be tied and fixed loops are no more than 7.5cm in circumference.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the shoulder straps, the strap including the loop shall lie flat to the body when worn.

Test Report No.: 27242903a 001

Page 31 of 55

M001c

- 3.3.6 Halter neck-style garments shall be constructed with no free ends at the neck and throat. The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment worn.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the halter neck strap, the strap including the loop shall lie flat to the body when worn.

3.4 Chest and waist area

- 3.4.1 Garments worn from waist down without shoulder straps, braces, or sleeves, such as trousers, shorts, skirts, briefs, bikini bottoms, shall not have:

a) Free ends of drawstrings longer than 20cm at each end when the garment is in a relaxed natural state;

N/A

b) Protruding loops on drawstrings with no free ends, when the garment is open to its largest and laid flat. Where toggles are used for adjustment of drawstrings with no free ends, the toggles shall be fixed to the garment;

N/A

c) Functional cords longer than 20cm;

N/A

d) Decorative cords longer than 14cm including any embellishment.

N/A

- 3.4.2 Garments other than those listed in 3.4.1 such as shirts, coats, dresses, and dungarees shall not have:

a) Free ends of drawstrings longer than 14cm at each end when the garment is open to its largest and laid flat;

N/A

b) Protruding loops on drawstrings with no free ends when the garment is open to its largest and laid flat. Where toggles are used for adjustment of drawstrings with no free ends, the toggles shall be fixed to the garment;

N/A

c) Functional cords longer than 14cm;

N/A

d) Decorative cords longer than 14cm including any embellishment.

N/A

- 3.4.3 For all garments, adjusting tabs in the waist area shall be a maximum of 14cm.

N/A

- 3.4.4 For young children, tied belts or sashes intended to be tied at the back of the garment are permissible provided that when untied and measured from the point where they are to be tied, they shall be no more than 36cm in length. When untied, they shall not hang below the hem of the garment.

N/A

- 3.4.5 For older children and young persons, tied belts or sashes intended to be tied at the back of the garment are permissible provided that, when untied and measured from the point where they are to be tied they shall be no more than 36cm in length.

N/A

- 3.4.6 For both age groups, tied belts or sashes intended to be tied at the front or at the side of the garment shall be acceptable provided that when untied they shall be no more than 36cm in length measured from the point where they are to be tied.

N/A

3.5 Lower hems of garments which hang below the crotch

Test Report No.: 27242903a 001

Page 32 of 55

M001c

- 3.5.1 Drawstrings, functional cords or decorative cords including any toggle shall not hang below the lower edge of the garment. N/A
- 3.5.2 Drawstrings, functional cords or decorative cords at the lower edges of garments shall lie flat against the garment, when the garment is tightened or fastened. N/A
- 3.5.3 In garments that are designed to finish at the ankle such as trousers, skirts or coats, the drawstrings, functional cords and decorative cords at the lower edge shall not be outside the garment. N/A
- 3.5.4 Adjusting tabs shall be no longer than 14cm, shall not hang below the lower edge of the garment and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. N/A
- 3.6 Back area**
- 3.6.1 Children's garments shall not be designed to have drawstrings or functional cords that emerge from the back of the garment or to be tied at the back. N/A
- 3.6.2 Decorative cords shall not be more than 7.5cm in length and shall have no knot, toggle or three dimensional embellishment. N/A
- 3.6.3 Adjusting tabs shall be no longer than 7.5cm, shall not hang below the lower edge of the garment and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. N/A
- 3.6.4 Tied belts or sashes are permissible (see 3.4.4 and 3.4.5). N/A
- 3.7 Sleeves**
- 3.7.1 Drawstrings, functional cords and decorative cords at the lower edge of long sleeves shall not be outside the garment, when the garment is fastened. N/A
- 3.7.2 Drawstrings, functional cords and decorative cords positioned below the elbow on long sleeves, shall not hang below the lower edge and free ends shall be no longer than 7.5cm. N/A
- 3.7.3 For younger children, drawstrings, functional cords and decorative cords are permissible on short sleeves provided the sleeve finishes above the elbow and the maximum protruding length is 7.5cm measured when the sleeve is open to its largest and laid flat. N/A
- 3.7.4 For older children and young persons, drawstrings, functional cords and decorative cords are permissible on short sleeves provided the sleeve finishes above the elbow and the maximum protruding length is 14cm measured when the sleeve is open to its largest and laid flat. N/A
- 3.7.5 For both age groups, adjusting tabs are permissible on sleeves provided that they are no longer than 10cm in length and when open shall not hang below the edge of the sleeve. N/A

3.8 Other parts of the garment

Test Report No.: 27242903a 001

Page 33 of 55

M001c

In all other areas of the garment, not previously addressed, the drawstring or functional and decorative cords shall protrude by no more than 14cm when the garment is open to its largest and laid flat.

N/A

Observation

No non-conformance to the requirements for EN 14682:2014 observed

Conclusion

Pass (Material M001c. It complies with the requirements for EN 14682:2014)

M001f**3.1 General**

3.1.1 The free ends of drawstrings, functional cords, and tied belts or sashes shall have no knots or three-dimensional embellishments and shall be secured to prevent fraying, for example by heat sealing or bar tacking. The ends may be doubled or folded provided no hazard of entrapment is created. Knots and three-dimensional embellishments along the length of the free ends are not permitted.

N/A

3.1.2 Toggles shall only be used on drawstrings with no free ends or decorative cords.

N/A

3.1.3 Where drawstrings are permitted, they shall be attached to the garment, for example using a bar tack, in at least one point positioned equidistant from the exit points.

N/A

3.1.4 Fixed loops, which protrude from the garment, for example to fasten, or loops on fixed bows, shall be no more than 7.5cm in circumference. Flat loops which do not protrude from the garments, for example for belt loops, shall be no more than 7.5cm in length, between the fixed points of attachment to the garment.

N/A

3.1.5 Zip pullers including any embellishment shall be no longer than 7.5cm in length from zip slider.

N/A

3.1.6 Zip pullers with or without embellishment shall not hang below the lower edge of garments designed to finish at the ankle.

N/A

3.2 Head, neck and upper chest area on garments for young children

3.2.1 Garments intended for young children shall not be designed, manufactured or supplied with drawstrings or functional cords in the head, neck or upper chest area.

N/A

3.2.2 Decorative cords shall not be permitted anywhere on the hood or at the back of the neck.

N/A

3.2.3 In other parts of neck and upper chest areas, decorative cords shall have free ends no longer than 7.5cm, shall have no knots, toggles or three dimensional embellishments and shall not be positioned so they can tie across the throat.

N/A

Decorative cords shall not be made from elastic cords.

3.2.4 Adjusting tabs are permissible provided that the length is no more than 7.5cm, and shall have no button, toggle, buckle on the free end which may present an entrapment hazard.

N/A

Test Report No.: 27242903a 001

Page 34 of 55

M001f

- 3.2.5 Shoulder straps shall be constructed such that, when worn, there shall be no free ends external to the garment. Shoulder straps may be permanently fixed to front and back, or attached to permit adjustment of strap length by for example buttons, press fasteners, provided the free end is inside the garment. The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment is worn.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the shoulder strap, the strap including the loop shall lie flat to the body when worn.

Decorative cords attached to a shoulder strap shall not have free ends longer than 7.5cm and fixed loops shall be no more than 7.5cm in circumference.

- 3.2.6 Halter neck-style garments shall be constructed with no free ends in the neck and throat.

N/A

The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment is worn.

Where a mechanism, for example ring and slider, is used to adjust the length of the halter neck, the strap including the loop shall lie flat to the body when worn.

3.3 Head, neck and upper chest area on garments for older children and young persons

- 3.3.1 Drawstrings shall not have free ends.

N/A

Drawstrings with no free ends shall have no protruding loop when the garment is open to its largest and laid flat. When the garment opening is at its smallest, i.e. the size it is intended to fit, maximum protruding loop circumference shall be 15cm.

Where toggles are used for adjustment of drawstrings with no free ends, the toggle shall be fixed to the garment.

- 3.3.2 Functional cords shall be not more than 7.5cm in length. Functional cords shall not be made from elastic cords.

N/A

- 3.3.3 Decorative cords shall not be more than 7.5cm in length including any attachment or three dimensional embellishment. Decorative cords shall not be made from elastic cords.

N/A

- 3.3.4 Adjusting tabs are permissible provided that the length is no more than 7.5cm, and shall have no button, toggle, buckle on the free end which may present an entrapment hazard.

N/A

- 3.3.5 Shoulder straps are permissible provided any free ends are no longer than 14cm from the point at which they are to be tied and fixed loops are no more than 7.5cm in circumference.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the shoulder straps, the strap including the loop shall lie flat to the body when worn.

Test Report No.: 27242903a 001

Page 35 of 55

M001f

- 3.3.6 Halter neck-style garments shall be constructed with no free ends at the neck and throat. The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment worn.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the halter neck strap, the strap including the loop shall lie flat to the body when worn.

3.4 Chest and waist area

- 3.4.1 Garments worn from waist down without shoulder straps, braces, or sleeves, such as trousers, shorts, skirts, briefs, bikini bottoms, shall not have:

a) Free ends of drawstrings longer than 20cm at each end when the garment is in a relaxed natural state;

N/A

b) Protruding loops on drawstrings with no free ends, when the garment is open to its largest and laid flat. Where toggles are used for adjustment of drawstrings with no free ends, the toggles shall be fixed to the garment;

N/A

c) Functional cords longer than 20cm;

N/A

d) Decorative cords longer than 14cm including any embellishment.

N/A

- 3.4.2 Garments other than those listed in 3.4.1 such as shirts, coats, dresses, and dungarees shall not have:

a) Free ends of drawstrings longer than 14cm at each end when the garment is open to its largest and laid flat;

N/A

b) Protruding loops on drawstrings with no free ends when the garment is open to its largest and laid flat. Where toggles are used for adjustment of drawstrings with no free ends, the toggles shall be fixed to the garment;

N/A

c) Functional cords longer than 14cm;

N/A

d) Decorative cords longer than 14cm including any embellishment.

N/A

- 3.4.3 For all garments, adjusting tabs in the waist area shall be a maximum of 14cm.

N/A

- 3.4.4 For young children, tied belts or sashes intended to be tied at the back of the garment are permissible provided that when untied and measured from the point where they are to be tied, they shall be no more than 36cm in length. When untied, they shall not hang below the hem of the garment.

N/A

- 3.4.5 For older children and young persons, tied belts or sashes intended to be tied at the back of the garment are permissible provided that, when untied and measured from the point where they are to be tied they shall be no more than 36cm in length.

N/A

- 3.4.6 For both age groups, tied belts or sashes intended to be tied at the front or at the side of the garment shall be acceptable provided that when untied they shall be no more than 36cm in length measured from the point where they are to be tied.

N/A

3.5 Lower hems of garments which hang below the crotch

Test Report No.: 27242903a 001

Page 36 of 55

M001f

- | | | |
|------------|---|-----|
| 3.5.1 | Drawstrings, functional cords or decorative cords including any toggle shall not hang below the lower edge of the garment. | N/A |
| 3.5.2 | Drawstrings, functional cords or decorative cords at the lower edges of garments shall lie flat against the garment, when the garment is tightened or fastened. | N/A |
| 3.5.3 | In garments that are designed to finish at the ankle such as trousers, skirts or coats, the drawstrings, functional cords and decorative cords at the lower edge shall not be outside the garment. | N/A |
| 3.5.4 | Adjusting tabs shall be no longer than 14cm, shall not hang below the lower edge of the garment and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. | N/A |
| 3.6 | Back area | |
| 3.6.1 | Children's garments shall not be designed to have drawstrings or functional cords that emerge from the back of the garment or to be tied at the back. | N/A |
| 3.6.2 | Decorative cords shall not be more than 7.5cm in length and shall have no knot, toggle or three dimensional embellishment. | N/A |
| 3.6.3 | Adjusting tabs shall be no longer than 7.5cm, shall not hang below the lower edge of the garment and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. | N/A |
| 3.6.4 | Tied belts or sashes are permissible (see 3.4.4 and 3.4.5). | N/A |
| 3.7 | Sleeves | |
| 3.7.1 | Drawstrings, functional cords and decorative cords at the lower edge of long sleeves shall not be outside the garment, when the garment is fastened. | N/A |
| 3.7.2 | Drawstrings, functional cords and decorative cords positioned below the elbow on long sleeves, shall not hang below the lower edge and free ends shall be no longer than 7.5cm. | N/A |
| 3.7.3 | For younger children, drawstrings, functional cords and decorative cords are permissible on short sleeves provided the sleeve finishes above the elbow and the maximum protruding length is 7.5cm measured when the sleeve is open to its largest and laid flat. | N/A |
| 3.7.4 | For older children and young persons, drawstrings, functional cords and decorative cords are permissible on short sleeves provided the sleeve finishes above the elbow and the maximum protruding length is 14cm measured when the sleeve is open to its largest and laid flat. | N/A |
| 3.7.5 | For both age groups, adjusting tabs are permissible on sleeves provided that they are no longer than 10cm in length and when open shall not hang below the edge of the sleeve. | N/A |
| 3.8 | Other parts of the garment | |

Test Report No.: 27242903a 001

Page 37 of 55

M001f

In all other areas of the garment, not previously addressed, the drawstring or functional and decorative cords shall protrude by no more than 14cm when the garment is open to its largest and laid flat.

N/A

Observation

No non-conformance to the requirements for EN 14682:2014 observed

Conclusion

Pass (Material M001f. It complies with the requirements for EN 14682:2014)

M001g**3.1 General**

3.1.1 The free ends of drawstrings, functional cords, and tied belts or sashes shall have no knots or three-dimensional embellishments and shall be secured to prevent fraying, for example by heat sealing or bar tacking. The ends may be doubled or folded provided no hazard of entrapment is created. Knots and three-dimensional embellishments along the length of the free ends are not permitted.

N/A

3.1.2 Toggles shall only be used on drawstrings with no free ends or decorative cords.

N/A

3.1.3 Where drawstrings are permitted, they shall be attached to the garment, for example using a bar tack, in at least one point positioned equidistant from the exit points.

N/A

3.1.4 Fixed loops, which protrude from the garment, for example to fasten, or loops on fixed bows, shall be no more than 7.5cm in circumference. Flat loops which do not protrude from the garments, for example for belt loops, shall be no more than 7.5cm in length, between the fixed points of attachment to the garment.

N/A

3.1.5 Zip pullers including any embellishment shall be no longer than 7.5cm in length from zip slider.

N/A

3.1.6 Zip pullers with or without embellishment shall not hang below the lower edge of garments designed to finish at the ankle.

N/A

3.2 Head, neck and upper chest area on garments for young children

3.2.1 Garments intended for young children shall not be designed, manufactured or supplied with drawstrings or functional cords in the head, neck or upper chest area.

N/A

3.2.2 Decorative cords shall not be permitted anywhere on the hood or at the back of the neck.

N/A

3.2.3 In other parts of neck and upper chest areas, decorative cords shall have free ends no longer than 7.5cm, shall have no knots, toggles or three dimensional embellishments and shall not be positioned so they can tie across the throat.

N/A

Decorative cords shall not be made from elastic cords.

3.2.4 Adjusting tabs are permissible provided that the length is no more than 7.5cm, and shall have no button, toggle, buckle on the free end which may present an entrapment hazard.

N/A

Test Report No.: 27242903a 001

Page 38 of 55

M001g

- 3.2.5 Shoulder straps shall be constructed such that, when worn, there shall be no free ends external to the garment. Shoulder straps may be permanently fixed to front and back, or attached to permit adjustment of strap length by for example buttons, press fasteners, provided the free end is inside the garment. The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment is worn.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the shoulder strap, the strap including the loop shall lie flat to the body when worn.

Decorative cords attached to a shoulder strap shall not have free ends longer than 7.5cm and fixed loops shall be no more than 7.5cm in circumference.

- 3.2.6 Halter neck-style garments shall be constructed with no free ends in the neck and throat.

N/A

The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment is worn.

Where a mechanism, for example ring and slider, is used to adjust the length of the halter neck, the strap including the loop shall lie flat to the body when worn.

3.3 Head, neck and upper chest area on garments for older children and young persons

- 3.3.1 Drawstrings shall not have free ends.

N/A

Drawstrings with no free ends shall have no protruding loop when the garment is open to its largest and laid flat. When the garment opening is at its smallest, i.e. the size it is intended to fit, maximum protruding loop circumference shall be 15cm.

Where toggles are used for adjustment of drawstrings with no free ends, the toggle shall be fixed to the garment.

- 3.3.2 Functional cords shall be not more than 7.5cm in length. Functional cords shall not be made from elastic cords.

N/A

- 3.3.3 Decorative cords shall not be more than 7.5cm in length including any attachment or three dimensional embellishment. Decorative cords shall not be made from elastic cords.

N/A

- 3.3.4 Adjusting tabs are permissible provided that the length is no more than 7.5cm, and shall have no button, toggle, buckle on the free end which may present an entrapment hazard.

N/A

- 3.3.5 Shoulder straps are permissible provided any free ends are no longer than 14cm from the point at which they are to be tied and fixed loops are no more than 7.5cm in circumference.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the shoulder straps, the strap including the loop shall lie flat to the body when worn.

Test Report No.: 27242903a 001

Page 39 of 55

M001g

- 3.3.6 Halter neck-style garments shall be constructed with no free ends at the neck and throat. The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment worn.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the halter neck strap, the strap including the loop shall lie flat to the body when worn.

3.4 Chest and waist area

- 3.4.1 Garments worn from waist down without shoulder straps, braces, or sleeves, such as trousers, shorts, skirts, briefs, bikini bottoms, shall not have:

a) Free ends of drawstrings longer than 20cm at each end when the garment is in a relaxed natural state;

N/A

b) Protruding loops on drawstrings with no free ends, when the garment is open to its largest and laid flat. Where toggles are used for adjustment of drawstrings with no free ends, the toggles shall be fixed to the garment;

N/A

c) Functional cords longer than 20cm;

N/A

d) Decorative cords longer than 14cm including any embellishment.

N/A

- 3.4.2 Garments other than those listed in 3.4.1 such as shirts, coats, dresses, and dungarees shall not have:

a) Free ends of drawstrings longer than 14cm at each end when the garment is open to its largest and laid flat;

N/A

b) Protruding loops on drawstrings with no free ends when the garment is open to its largest and laid flat. Where toggles are used for adjustment of drawstrings with no free ends, the toggles shall be fixed to the garment;

N/A

c) Functional cords longer than 14cm;

N/A

d) Decorative cords longer than 14cm including any embellishment.

N/A

- 3.4.3 For all garments, adjusting tabs in the waist area shall be a maximum of 14cm.

N/A

- 3.4.4 For young children, tied belts or sashes intended to be tied at the back of the garment are permissible provided that when untied and measured from the point where they are to be tied, they shall be no more than 36cm in length. When untied, they shall not hang below the hem of the garment.

N/A

- 3.4.5 For older children and young persons, tied belts or sashes intended to be tied at the back of the garment are permissible provided that, when untied and measured from the point where they are to be tied they shall be no more than 36cm in length.

N/A

- 3.4.6 For both age groups, tied belts or sashes intended to be tied at the front or at the side of the garment shall be acceptable provided that when untied they shall be no more than 36cm in length measured from the point where they are to be tied.

N/A

3.5 Lower hems of garments which hang below the crotch

Test Report No.: 27242903a 001

Page 40 of 55

M001g

- 3.5.1 Drawstrings, functional cords or decorative cords including any toggle shall not hang below the lower edge of the garment. N/A
- 3.5.2 Drawstrings, functional cords or decorative cords at the lower edges of garments shall lie flat against the garment, when the garment is tightened or fastened. N/A
- 3.5.3 In garments that are designed to finish at the ankle such as trousers, skirts or coats, the drawstrings, functional cords and decorative cords at the lower edge shall not be outside the garment. N/A
- 3.5.4 Adjusting tabs shall be no longer than 14cm, shall not hang below the lower edge of the garment and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. N/A
- 3.6 Back area**
- 3.6.1 Children's garments shall not be designed to have drawstrings or functional cords that emerge from the back of the garment or to be tied at the back. N/A
- 3.6.2 Decorative cords shall not be more than 7.5cm in length and shall have no knot, toggle or three dimensional embellishment. N/A
- 3.6.3 Adjusting tabs shall be no longer than 7.5cm, shall not hang below the lower edge of the garment and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. N/A
- 3.6.4 Tied belts or sashes are permissible (see 3.4.4 and 3.4.5). N/A
- 3.7 Sleeves**
- 3.7.1 Drawstrings, functional cords and decorative cords at the lower edge of long sleeves shall not be outside the garment, when the garment is fastened. N/A
- 3.7.2 Drawstrings, functional cords and decorative cords positioned below the elbow on long sleeves, shall not hang below the lower edge and free ends shall be no longer than 7.5cm. N/A
- 3.7.3 For younger children, drawstrings, functional cords and decorative cords are permissible on short sleeves provided the sleeve finishes above the elbow and the maximum protruding length is 7.5cm measured when the sleeve is open to its largest and laid flat. N/A
- 3.7.4 For older children and young persons, drawstrings, functional cords and decorative cords are permissible on short sleeves provided the sleeve finishes above the elbow and the maximum protruding length is 14cm measured when the sleeve is open to its largest and laid flat. N/A
- 3.7.5 For both age groups, adjusting tabs are permissible on sleeves provided that they are no longer than 10cm in length and when open shall not hang below the edge of the sleeve. N/A

3.8 Other parts of the garment

Test Report No.: 27242903a 001

Page 41 of 55

M001g

In all other areas of the garment, not previously addressed, the drawstring or functional and decorative cords shall protrude by no more than 14cm when the garment is open to its largest and laid flat.

N/A

Observation

No non-conformance to the requirements for EN 14682:2014 observed

Conclusion

Pass (Material M001g. It complies with the requirements for EN 14682:2014)

M001d-1**3.1 General**

3.1.1 The free ends of drawstrings, functional cords, and tied belts or sashes shall have no knots or three-dimensional embellishments and shall be secured to prevent fraying, for example by heat sealing or bar tacking. The ends may be doubled or folded provided no hazard of entrapment is created. Knots and three-dimensional embellishments along the length of the free ends are not permitted.

N/A

3.1.2 Toggles shall only be used on drawstrings with no free ends or decorative cords.

N/A

3.1.3 Where drawstrings are permitted, they shall be attached to the garment, for example using a bar tack, in at least one point positioned equidistant from the exit points.

N/A

3.1.4 Fixed loops, which protrude from the garment, for example to fasten, or loops on fixed bows, shall be no more than 7.5cm in circumference. Flat loops which do not protrude from the garments, for example for belt loops, shall be no more than 7.5cm in length, between the fixed points of attachment to the garment.

P

3.1.5 Zip pullers including any embellishment shall be no longer than 7.5cm in length from zip slider.

N/A

3.1.6 Zip pullers with or without embellishment shall not hang below the lower edge of garments designed to finish at the ankle.

N/A

3.2 Head, neck and upper chest area on garments for young children

3.2.1 Garments intended for young children shall not be designed, manufactured or supplied with drawstrings or functional cords in the head, neck or upper chest area.

N/A

3.2.2 Decorative cords shall not be permitted anywhere on the hood or at the back of the neck.

N/A

3.2.3 In other parts of neck and upper chest areas, decorative cords shall have free ends no longer than 7.5cm, shall have no knots, toggles or three dimensional embellishments and shall not be positioned so they can tie across the throat.

N/A

Decorative cords shall not be made from elastic cords.

3.2.4 Adjusting tabs are permissible provided that the length is no more than 7.5cm, and shall have no button, toggle, buckle on the free end which may present an entrapment hazard.

N/A

Test Report No.: 27242903a 001

Page 42 of 55

M001d-1

- 3.2.5 Shoulder straps shall be constructed such that, when worn, there shall be no free ends external to the garment. Shoulder straps may be permanently fixed to front and back, or attached to permit adjustment of strap length by for example buttons, press fasteners, provided the free end is inside the garment. The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment is worn.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the shoulder strap, the strap including the loop shall lie flat to the body when worn.

Decorative cords attached to a shoulder strap shall not have free ends longer than 7.5cm and fixed loops shall be no more than 7.5cm in circumference.

- 3.2.6 Halter neck-style garments shall be constructed with no free ends in the neck and throat.

N/A

The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment is worn.

Where a mechanism, for example ring and slider, is used to adjust the length of the halter neck, the strap including the loop shall lie flat to the body when worn.

3.3 Head, neck and upper chest area on garments for older children and young persons

- 3.3.1 Drawstrings shall not have free ends.

N/A

Drawstrings with no free ends shall have no protruding loop when the garment is open to its largest and laid flat. When the garment opening is at its smallest, i.e. the size it is intended to fit, maximum protruding loop circumference shall be 15cm.

Where toggles are used for adjustment of drawstrings with no free ends, the toggle shall be fixed to the garment.

- 3.3.2 Functional cords shall be not more than 7.5cm in length. Functional cords shall not be made from elastic cords.

N/A

- 3.3.3 Decorative cords shall not be more than 7.5cm in length including any attachment or three dimensional embellishment. Decorative cords shall not be made from elastic cords.

N/A

- 3.3.4 Adjusting tabs are permissible provided that the length is no more than 7.5cm, and shall have no button, toggle, buckle on the free end which may present an entrapment hazard.

N/A

- 3.3.5 Shoulder straps are permissible provided any free ends are no longer than 14cm from the point at which they are to be tied and fixed loops are no more than 7.5cm in circumference.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the shoulder straps, the strap including the loop shall lie flat to the body when worn.

Test Report No.: 27242903a 001

Page 43 of 55

M001d-1

- 3.3.6 Halter neck-style garments shall be constructed with no free ends at the neck and throat. The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment worn.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the halter neck strap, the strap including the loop shall lie flat to the body when worn.

3.4 Chest and waist area

- 3.4.1 Garments worn from waist down without shoulder straps, braces, or sleeves, such as trousers, shorts, skirts, briefs, bikini bottoms, shall not have:

a) Free ends of drawstrings longer than 20cm at each end when the garment is in a relaxed natural state;

N/A

b) Protruding loops on drawstrings with no free ends, when the garment is open to its largest and laid flat. Where toggles are used for adjustment of drawstrings with no free ends, the toggles shall be fixed to the garment;

N/A

c) Functional cords longer than 20cm;

N/A

d) Decorative cords longer than 14cm including any embellishment.

N/A

- 3.4.2 Garments other than those listed in 3.4.1 such as shirts, coats, dresses, and dungarees shall not have:

a) Free ends of drawstrings longer than 14cm at each end when the garment is open to its largest and laid flat;

N/A

b) Protruding loops on drawstrings with no free ends when the garment is open to its largest and laid flat. Where toggles are used for adjustment of drawstrings with no free ends, the toggles shall be fixed to the garment;

N/A

c) Functional cords longer than 14cm;

N/A

d) Decorative cords longer than 14cm including any embellishment.

N/A

- 3.4.3 For all garments, adjusting tabs in the waist area shall be a maximum of 14cm.

N/A

- 3.4.4 For young children, tied belts or sashes intended to be tied at the back of the garment are permissible provided that when untied and measured from the point where they are to be tied, they shall be no more than 36cm in length. When untied, they shall not hang below the hem of the garment.

N/A

- 3.4.5 For older children and young persons, tied belts or sashes intended to be tied at the back of the garment are permissible provided that, when untied and measured from the point where they are to be tied they shall be no more than 36cm in length.

N/A

- 3.4.6 For both age groups, tied belts or sashes intended to be tied at the front or at the side of the garment shall be acceptable provided that when untied they shall be no more than 36cm in length measured from the point where they are to be tied.

N/A

3.5 Lower hems of garments which hang below the crotch

Test Report No.: 27242903a 001

Page 44 of 55

M001d-1

- | | | |
|---------------------------------------|---|-----|
| 3.5.1 | Drawstrings, functional cords or decorative cords including any toggle shall not hang below the lower edge of the garment. | N/A |
| 3.5.2 | Drawstrings, functional cords or decorative cords at the lower edges of garments shall lie flat against the garment, when the garment is tightened or fastened. | N/A |
| 3.5.3 | In garments that are designed to finish at the ankle such as trousers, skirts or coats, the drawstrings, functional cords and decorative cords at the lower edge shall not be outside the garment. | N/A |
| 3.5.4 | Adjusting tabs shall be no longer than 14cm, shall not hang below the lower edge of the garment and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. | N/A |
| 3.6 Back area | | |
| 3.6.1 | Children's garments shall not be designed to have drawstrings or functional cords that emerge from the back of the garment or to be tied at the back. | N/A |
| 3.6.2 | Decorative cords shall not be more than 7.5cm in length and shall have no knot, toggle or three dimensional embellishment. | N/A |
| 3.6.3 | Adjusting tabs shall be no longer than 7.5cm, shall not hang below the lower edge of the garment and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. | N/A |
| 3.6.4 | Tied belts or sashes are permissible (see 3.4.4 and 3.4.5). | N/A |
| 3.7 Sleeves | | |
| 3.7.1 | Drawstrings, functional cords and decorative cords at the lower edge of long sleeves shall not be outside the garment, when the garment is fastened. | N/A |
| 3.7.2 | Drawstrings, functional cords and decorative cords positioned below the elbow on long sleeves, shall not hang below the lower edge and free ends shall be no longer than 7.5cm. | N/A |
| 3.7.3 | For younger children, drawstrings, functional cords and decorative cords are permissible on short sleeves provided the sleeve finishes above the elbow and the maximum protruding length is 7.5cm measured when the sleeve is open to its largest and laid flat. | N/A |
| 3.7.4 | For older children and young persons, drawstrings, functional cords and decorative cords are permissible on short sleeves provided the sleeve finishes above the elbow and the maximum protruding length is 14cm measured when the sleeve is open to its largest and laid flat. | N/A |
| 3.7.5 | For both age groups, adjusting tabs are permissible on sleeves provided that they are no longer than 10cm in length and when open shall not hang below the edge of the sleeve. | N/A |
| 3.8 Other parts of the garment | | |

Test Report No.: 27242903a 001

Page 45 of 55

M001d-1

In all other areas of the garment, not previously addressed, the drawstring or functional and decorative cords shall protrude by no more than 14cm when the garment is open to its largest and laid flat.

N/A

Observation

No non-conformance to the requirements for EN 14682:2014 observed

Conclusion

Pass (Material M001d-1. It complies with the requirements for EN 14682:2014)

M001e-1**3.1 General**

3.1.1 The free ends of drawstrings, functional cords, and tied belts or sashes shall have no knots or three-dimensional embellishments and shall be secured to prevent fraying, for example by heat sealing or bar tacking. The ends may be doubled or folded provided no hazard of entrapment is created. Knots and three-dimensional embellishments along the length of the free ends are not permitted.

N/A

3.1.2 Toggles shall only be used on drawstrings with no free ends or decorative cords.

N/A

3.1.3 Where drawstrings are permitted, they shall be attached to the garment, for example using a bar tack, in at least one point positioned equidistant from the exit points.

N/A

3.1.4 Fixed loops, which protrude from the garment, for example to fasten, or loops on fixed bows, shall be no more than 7.5cm in circumference. Flat loops which do not protrude from the garments, for example for belt loops, shall be no more than 7.5cm in length, between the fixed points of attachment to the garment.

P

3.1.5 Zip pullers including any embellishment shall be no longer than 7.5cm in length from zip slider.

N/A

3.1.6 Zip pullers with or without embellishment shall not hang below the lower edge of garments designed to finish at the ankle.

N/A

3.2 Head, neck and upper chest area on garments for young children

3.2.1 Garments intended for young children shall not be designed, manufactured or supplied with drawstrings or functional cords in the head, neck or upper chest area.

N/A

3.2.2 Decorative cords shall not be permitted anywhere on the hood or at the back of the neck.

N/A

3.2.3 In other parts of neck and upper chest areas, decorative cords shall have free ends no longer than 7.5cm, shall have no knots, toggles or three dimensional embellishments and shall not be positioned so they can tie across the throat.

N/A

Decorative cords shall not be made from elastic cords.

3.2.4 Adjusting tabs are permissible provided that the length is no more than 7.5cm, and shall have no button, toggle, buckle on the free end which may present an entrapment hazard.

N/A

Test Report No.: 27242903a 001

Page 46 of 55

M001e-1

- 3.2.5 Shoulder straps shall be constructed such that, when worn, there shall be no free ends external to the garment. Shoulder straps may be permanently fixed to front and back, or attached to permit adjustment of strap length by for example buttons, press fasteners, provided the free end is inside the garment. The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment is worn.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the shoulder strap, the strap including the loop shall lie flat to the body when worn.

Decorative cords attached to a shoulder strap shall not have free ends longer than 7.5cm and fixed loops shall be no more than 7.5cm in circumference.

- 3.2.6 Halter neck-style garments shall be constructed with no free ends in the neck and throat.

N/A

The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment is worn.

Where a mechanism, for example ring and slider, is used to adjust the length of the halter neck, the strap including the loop shall lie flat to the body when worn.

3.3 Head, neck and upper chest area on garments for older children and young persons

- 3.3.1 Drawstrings shall not have free ends.

N/A

Drawstrings with no free ends shall have no protruding loop when the garment is open to its largest and laid flat. When the garment opening is at its smallest, i.e. the size it is intended to fit, maximum protruding loop circumference shall be 15cm.

Where toggles are used for adjustment of drawstrings with no free ends, the toggle shall be fixed to the garment.

- 3.3.2 Functional cords shall be not more than 7.5cm in length. Functional cords shall not be made from elastic cords.

N/A

- 3.3.3 Decorative cords shall not be more than 7.5cm in length including any attachment or three dimensional embellishment. Decorative cords shall not be made from elastic cords.

N/A

- 3.3.4 Adjusting tabs are permissible provided that the length is no more than 7.5cm, and shall have no button, toggle, buckle on the free end which may present an entrapment hazard.

N/A

- 3.3.5 Shoulder straps are permissible provided any free ends are no longer than 14cm from the point at which they are to be tied and fixed loops are no more than 7.5cm in circumference.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the shoulder straps, the strap including the loop shall lie flat to the body when worn.

Test Report No.: 27242903a 001

Page 47 of 55

M001e-1

- 3.3.6 Halter neck-style garments shall be constructed with no free ends at the neck and throat. The use of a clip or fastening of two cords is acceptable, provided these do not result in free ends of cords when garment worn.

N/A

Where a mechanism, for example ring and slider, is used to adjust the length of the halter neck strap, the strap including the loop shall lie flat to the body when worn.

3.4 Chest and waist area

- 3.4.1 Garments worn from waist down without shoulder straps, braces, or sleeves, such as trousers, shorts, skirts, briefs, bikini bottoms, shall not have:

a) Free ends of drawstrings longer than 20cm at each end when the garment is in a relaxed natural state;

N/A

b) Protruding loops on drawstrings with no free ends, when the garment is open to its largest and laid flat. Where toggles are used for adjustment of drawstrings with no free ends, the toggles shall be fixed to the garment;

N/A

c) Functional cords longer than 20cm;

N/A

d) Decorative cords longer than 14cm including any embellishment.

N/A

- 3.4.2 Garments other than those listed in 3.4.1 such as shirts, coats, dresses, and dungarees shall not have:

a) Free ends of drawstrings longer than 14cm at each end when the garment is open to its largest and laid flat;

N/A

b) Protruding loops on drawstrings with no free ends when the garment is open to its largest and laid flat. Where toggles are used for adjustment of drawstrings with no free ends, the toggles shall be fixed to the garment;

N/A

c) Functional cords longer than 14cm;

N/A

d) Decorative cords longer than 14cm including any embellishment.

N/A

- 3.4.3 For all garments, adjusting tabs in the waist area shall be a maximum of 14cm.

N/A

- 3.4.4 For young children, tied belts or sashes intended to be tied at the back of the garment are permissible provided that when untied and measured from the point where they are to be tied, they shall be no more than 36cm in length. When untied, they shall not hang below the hem of the garment.

N/A

- 3.4.5 For older children and young persons, tied belts or sashes intended to be tied at the back of the garment are permissible provided that, when untied and measured from the point where they are to be tied they shall be no more than 36cm in length.

N/A

- 3.4.6 For both age groups, tied belts or sashes intended to be tied at the front or at the side of the garment shall be acceptable provided that when untied they shall be no more than 36cm in length measured from the point where they are to be tied.

N/A

3.5 Lower hems of garments which hang below the crotch

Test Report No.: 27242903a 001

Page 48 of 55

M001e-1

- | | | |
|------------|---|-----|
| 3.5.1 | Drawstrings, functional cords or decorative cords including any toggle shall not hang below the lower edge of the garment. | N/A |
| 3.5.2 | Drawstrings, functional cords or decorative cords at the lower edges of garments shall lie flat against the garment, when the garment is tightened or fastened. | N/A |
| 3.5.3 | In garments that are designed to finish at the ankle such as trousers, skirts or coats, the drawstrings, functional cords and decorative cords at the lower edge shall not be outside the garment. | N/A |
| 3.5.4 | Adjusting tabs shall be no longer than 14cm, shall not hang below the lower edge of the garment and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. | N/A |
| 3.6 | Back area | |
| 3.6.1 | Children's garments shall not be designed to have drawstrings or functional cords that emerge from the back of the garment or to be tied at the back. | N/A |
| 3.6.2 | Decorative cords shall not be more than 7.5cm in length and shall have no knot, toggle or three dimensional embellishment. | N/A |
| 3.6.3 | Adjusting tabs shall be no longer than 7.5cm, shall not hang below the lower edge of the garment and shall have no button, toggle, buckle on the free end which may present an entrapment hazard. | N/A |
| 3.6.4 | Tied belts or sashes are permissible (see 3.4.4 and 3.4.5). | N/A |
| 3.7 | Sleeves | |
| 3.7.1 | Drawstrings, functional cords and decorative cords at the lower edge of long sleeves shall not be outside the garment, when the garment is fastened. | N/A |
| 3.7.2 | Drawstrings, functional cords and decorative cords positioned below the elbow on long sleeves, shall not hang below the lower edge and free ends shall be no longer than 7.5cm. | N/A |
| 3.7.3 | For younger children, drawstrings, functional cords and decorative cords are permissible on short sleeves provided the sleeve finishes above the elbow and the maximum protruding length is 7.5cm measured when the sleeve is open to its largest and laid flat. | N/A |
| 3.7.4 | For older children and young persons, drawstrings, functional cords and decorative cords are permissible on short sleeves provided the sleeve finishes above the elbow and the maximum protruding length is 14cm measured when the sleeve is open to its largest and laid flat. | N/A |
| 3.7.5 | For both age groups, adjusting tabs are permissible on sleeves provided that they are no longer than 10cm in length and when open shall not hang below the edge of the sleeve. | N/A |
| 3.8 | Other parts of the garment | |

Test Report No.: 27242903a 001

Page 49 of 55

M001e-1

N/A

In all other areas of the garment, not previously addressed, the drawstring or functional and decorative cords shall protrude by no more than 14cm when the garment is open to its largest and laid flat.

Observation

No non-conformance to the requirements for EN 14682:2014 observed

Conclusion

Pass (Material M001e-1. It complies with the requirements for EN 14682:2014)

Remark : P = Pass
F = Fail
N/A = Not applicable
= Submitted sample without labelling / with mock up labelling

The test is not covered by CNAS accreditation.

Testing Laboratory accredited by CNAS according to ISO/IEC 17025. The accreditation is valid for the test methods stated in the certificate.

Test Report No.: 27242903a 001

Page 50 of 55

Sample Photos



Test Report No.: 27242903a 001

Page 51 of 55

Sample Photos



Test Report No.: 27242903a 001

Page 52 of 55

Sample Photos



Reference photo provided by client

Test Report No.: 27242903a 001

Page 53 of 55

Sample Photos



Reference photo provided by client



Reference photo provided by client



Reference photo provided by client



Reference photo provided by client



Reference photo provided by client



Reference photo provided by client

Test Report No.: 27242903a 001

Page 54 of 55

Sample Photos



Reference photo provided by client



Reference photo provided by client



Reference photo provided by client



Reference photo provided by client



Reference photo provided by client



Reference photo provided by client

Test Report No.: 27242903a 001

Page 55 of 55

Sample Photos



Reference photo provided by client



Reference photo provided by client



Reference photo provided by client

- END -

